

WIND DATA REPORT

Swan's Island, ME

December 1, 2008 – February 28, 2009

Prepared for

US Department of Energy

by

Daniel T. Grip
Utama Abdulwahid
James F. Manwell
Anthony F. Ellis

September 16, 2009

Report template version 3.1.1

Renewable Energy Research Laboratory
University of Massachusetts, Amherst
160 Governors Drive, Amherst, MA 01003

www.ceere.org/rerl • (413) 545-4359 • rerl@ecs.umass.edu



NOTICE AND ACKNOWLEDGEMENTS

This report was prepared by the Renewable Energy Research Laboratory (RERL) at the University of Massachusetts, Amherst in the course of performing work sponsored by the US Department of Energy. The opinions expressed in this report do not necessarily reflect those of the US DOE and reference to any specific product, service, process, or method does not constitute an implied or expressed recommendation or endorsement of it.

Further, the US DOE, and RERL make no warranties or representations, expressed or implied, as to the fitness for particular purpose or merchantability of any product, apparatus, or service, or the usefulness, completeness, or accuracy of any processes, methods or other information contained, described, disclosed, or referred to in this report. The US DOE and RERL make no representation that the use of any product, apparatus, process, method, or other information will not infringe privately owned rights and will assume no liability for any loss, injury, or damage directly or indirectly resulting from, or occurring in connection with, the use of information contained, described, disclosed, or referred to in this report.

TABLE OF CONTENTS

Notice and Acknowledgements	1
Table of Contents	2
Table of Figures	3
Executive Summary	4
SECTION 1 - Station Location	5
SECTION 2 - Instrumentation and Equipment	5
SECTION 3 - Data Summary	6
SECTION 4 - Graphs	8
Wind Speed Time Series	9
Wind Speed Distributions	10
Monthly Average Wind Speeds	10
Diurnal Average Wind Speeds	11
Turbulence Intensities	11
Wind Roses	12
SECTION 5 - Significant Meteorological Events	12
SECTION 6 - Data Collection and Maintenance	13
SECTION 7 - Data Recovery and Validation	13
Test Definitions	13
Sensor Statistics	14
APPENDIX A - Sensor Performance Report	16
Test Definitions	16
Sensor Statistics	17
APPENDIX B - Plot Data	18
Wind Speed Distribution Data	18
Diurnal Average Wind Speed Data	18
Monthly Average Wind Speed Data	19
Wind Rose Data	20

TABLE OF FIGURES

Figure 1 - Location of the Swans Island Tower.....	5
Figure 2 – Wind Speed Time Series, December 1, 2008 – February 28, 2009	9
Figure 3 – Wind Speed Distribution, December 1, 2008 – February 28, 2009	10
Figure 4 – Monthly Average Wind Speed September 2007 – February 2009.....	10
Figure 5 – Diurnal Average Wind Speed, December 1, 2008 – February 28, 2009	11
Figure 6 – Turbulence Intensity, December 1, 2008 – February 28, 2009	11
Figure 7 – Wind Rose, December 1, 2008 – February 28, 2009	12

EXECUTIVE SUMMARY

All the work presented in this Wind Data Report including installation and decommissioning of the meteorological tower and instrumentation, and the data analysis and reporting was performed by the Renewable Energy Research Laboratory (RERL) at the University of Massachusetts, Amherst.

This report summarizes the wind data recorded for the winter quarter, December 2008 through February 2009, at Swan's Island, ME. The winter months showed a significant increase in wind resource from the fall quarter. Average wind speeds were found to be around 8 m/s at a height of 50m. The prevailing wind direction for the quarter was NNW. The amount of valid data recorded for the quarter was 92%. Some months were extremely cold resulting in some icing that lowered the amount of valid data.

Additional information about interpreting the data presented in this report can be found in the Fact Sheet, "Interpreting Your Wind Resource Data," produced by RERL and the Massachusetts Technology Collaborative (MTC). This document is found through the RERL website:

http://www.ceere.org/rerl/about_wind/RERL_Fact_Sheet_6_Wind_resource_interpretation.pdf

* 1 m/s = 2.237 mph.

SECTION 1 - Station Location

The station is a cell phone tower operated by U.S. Cellular, located at Stockbridge Hill on Swans Island, Maine. The coordinates for the tower are 44.11161 N, 68.42218 W. The base of the tower is at an altitude of 54.86 m (180 ft) above mean sea level.



Figure 1 - Location of the Swans Island Tower

SECTION 2- Instrumentation and Equipment

The wind monitoring equipment is mounted on the cell phone tower at a height of 50 m and 40 m. At each height 2 NRG #40 anemometers with standard calibration (Slope – 0.765 m/s, Offset – 0.350 m/s) and 1 NRG #200P wind vane are installed. A #110S temperature sensor is mounted at the base of the tower at an approximated height of 2 m. The data is logged by an NRG Symphonie logger and is mailed to the University of Massachusetts, Amherst on a regular basis. The logger samples wind speed and direction once every two seconds. These samples are combined into 10-minute averages and are put into a binary file along with the standard deviation for each 10-minute interval. The binary files are converted to ASCII text files using the NRG software BaseStation®.

These text files are then imported into a database software program where they are subjected to quality assurance tests prior to data usage.

SECTION 3- Data Summary

A summary of the wind speeds and wind directions measured during the reporting period is included in Table 1. Table 1 includes the mean wind speeds measured at each measurement height, the maximum instantaneous wind speed measured at each measurement height and the prevailing wind direction measured at each measurement height. These values are provided for each month of the reporting period and for the whole reporting period.

Table 1. Wind Speed and Direction Data Summary

Date	Mean Wind Speed	Max Wind Speed	Prevailing Wind Direction	Mean Wind Speed	Max Wind Speed	Prevailing Wind Direction
Height Units	50 m [m/s]	50 m [m/s]	50 m	40 m [m/s]	40 m [m/s]	40 m
Dec 2008	8.75	21.34	SW	7.99	19.72	NW
Jan 2009	7.38	19.69	NNW	6.92	18.39*	NW*
Feb 2009	7.69	17.65	NNW	7.02	16.32*	NW*
Dec 2008 -Feb 2009	7.95	21.34	NNW	7.33	19.72	NW

* Less than 90% data

Wind data statistics in the table are reported when more than 90% of the data during the reporting period are valid. In cases when larger amounts of data are missing, the percent of the available data that are used to determine the data statistics is noted. For this quarter, the data marked as less than 90% valid varied from 88.9% to 89.8%. This is due primarily to icing.

No measurement of wind speed or direction can be perfectly accurate. Wind speed measurement errors occur due to anemometer manufacturing variability, anemometer calibration errors, the response of anemometers to turbulence and vertical air flow and due to air flows caused by the anemometer mounting system. Every effort is made to reduce the sources of these errors. Nevertheless, the values reported in this report have an expected uncertainty of about $\pm 2\%$ or ± 0.2 m/s, whichever is greater. Wind direction measurement errors occur due to sensor measurement uncertainty, tower effects, boom alignment measurement errors and twisting of pipe sections during the raising of a pipe tower. Efforts are also made to reduce these errors, but the reported wind directions are estimated to have an uncertainty of ± 5 degrees.

A summary of the turbulence intensity and mean wind shear measured at each measurement height during the reporting period is included in Table 2. These values are provided for each month of the reporting period and for the whole reporting period. Turbulence Intensity is calculated by dividing the standard deviation of the wind speed by the mean wind speed and is a measure of the gustiness of a wind resource. Lower turbulence results in lower mechanical loads on a wind turbine. Turbulence intensity varies with wind speed. The average turbulence intensity presented in Table 2 is the mean turbulence intensity when the wind speed at each measurement height is between 10 and 11 m/s.

Shear coefficients provide a measure of the change in wind speed with height. When data at multiple heights are available, shear coefficients, α , have been determined. They can be used in the following formula to estimate the average wind speed, $U(z)$, at height z , when the average wind speed, $U(z_r)$, at height z_r is known:

$$U(z) = U(z_r) \left(\frac{z}{z_r} \right)^\alpha$$

The change in wind speed with height is a very complicated relationship related to atmospheric conditions, wind speed, wind direction, time of day and time of year. This formula will not always provide the correct answer at any given site. Nevertheless the calculated shear coefficient, based on measurements at two heights, can be used to characterize the degree of increase in wind speed with height at a site.

The mean wind shear coefficient that is provided here is calculated based on the mean wind speeds in Table 1, where z_{high} and z_{low} are the heights of the higher and lower mean wind speeds used in the calculation and $U(z_{low})$ and $U(z_{high})$ are the mean wind speeds at the two heights.

$$\alpha = \log \left(\frac{U(z_{high})}{U(z_{low})} \right) / \log \left(\frac{z_{high}}{z_{low}} \right)$$

Table 2. Shear and Turbulence Intensity Data Summary

Date	Turbulence Intensity at 10 m/s	Turbulence Intensity at 10 m/s	Mean Wind Shear Coefficient, α
Height Units	50 m [-]	40 m [-]	Between 50 m and 40 m [-]
Dec 2008	0.17	0.19	0.41
Jan 2009	0.16	0.18	0.29
Feb 2009	0.15	0.18	0.41
Dec 2008 -Feb 2009	0.16	0.18	0.36

SECTION 4- Graphs

This report contains several types of wind data graphs. Unless otherwise noted, each graph represents data from 1 quarter (3 months). The following graphs are included:

- Time Series – 10-minute average wind speeds are plotted against time.
- Wind Speed Distribution – A histogram plot giving the percentage of time that the wind is at a given wind speed.
- Monthly Average – A plot of the monthly average wind speed over a 12-month period. This graph shows the trends in the wind speed over the year.
- Diurnal – A plot of the average wind speed for each hour of the day.
- Turbulence Intensity – A plot of turbulence intensity as a function of wind speed. Turbulence Intensity is calculated as the standard deviation of the wind speed divided by the wind speed and is a measure of the gustiness of a wind resource. Lower turbulence results in lower mechanical loads on a wind turbine.
- Wind Rose – A plot, by compass direction showing the percentage of time that the wind comes from a given direction and the average wind speed in that direction.

The time series shows the wind to stay between 5-10 m/s for the majority of the time with some highs above 15 m/s, especially in December. The monthly averages for the winter have increased significantly from the fall. The mean wind speeds hold fairly steady over the hours of the day with a high point just after noon and a low point around sunrise. The

wind rose displays the prevailing wind direction of NNW where the winds are around the average speed (approximately 8.0 m/s) although stronger winds are shown to come from the East.

Data for the wind speed histograms, monthly and diurnal average plots, and wind roses are included in APPENDIX B.

Wind Speed Time Series




Figure 2 – Wind Speed Time Series, December 1, 2008 – February 28, 2009

Wind Speed Distributions




Figure 3 – Wind Speed Distribution, December 1, 2008 – February 28, 2009

Monthly Average Wind Speeds




Figure 4 – Monthly Average Wind Speed September 2007 – February 2009

Diurnal Average Wind Speeds




Figure 5 – Diurnal Average Wind Speed, December 1, 2008 – February 28, 2009

Turbulence Intensities




Figure 6 – Turbulence Intensity, December 1, 2008 – February 28, 2009

Wind Roses




Figure 7 – Wind Rose, December 1, 2008 – February 28, 2009

SECTION 5- Significant Meteorological Events

There were no significant meteorological events reported in the region between December 2008 and February 2009. January was an extremely cold month with some of the coldest recorded temperatures on record.

Source: <http://www.weather.gov/climate/index.php?wfo=car>

SECTION 6 - Data Collection and Maintenance

There were no maintenance issues with the equipment for this quarter and data collection went well.

SECTION 7 - Data Recovery and Validation

All raw wind data are subjected to a series of tests and filters to weed out data that are faulty or corrupted. Definitions of these quality assurance (QA) controls are given below under Test Definitions and Sensor Statistics. These control filters were designed to automate the quality control process and used many of the previous hand-worked data sets made at UMass to affect a suitable emulation. The gross percentage of data recovered (ratio of the number of raw data points received to data points expected) and net percentage (ratio of raw data points which passed all QA control tests to data points expected) are shown below.

Gross Data Recovered [%]	100
Net Data Recovered [%]	91.88

Test Definitions

All raw data were subjected to a series of validation tests, as described below. The sensors tested and the parameters specific to each sensor are given in the Sensor Performance Report which is included in APPENDIX A. Data which were flagged as invalid were not included in the statistics presented in this report.

MinMax Test: All sensors are expected to report data values within a range specified by the sensor and logger manufacturers. If a value falls outside this range, it is flagged as invalid. A data value from the sensor listed in Test Field 1 (TF1) is flagged if it is less than Factor 1 (F1) or greater than Factor 2. This test has been applied to the following sensors (as applicable): wind speed, wind speed standard deviation, wind direction, temperature, and solar insolation.

$$F1 > TF1 > F2$$

MinMaxT Test: This is a MinMax test for wind direction standard deviation with different ranges applied for high and low wind speeds. A wind direction standard deviation data value (TF1) is flagged either if it is less than Factor 1, if the wind speed (TF2) is less than Factor 4 and the wind direction standard deviation is greater than Factor 2, or if the wind speed is greater than or equal to Factor 4 and the wind direction standard deviation is greater than Factor 3.

$$\begin{aligned}
 & (\text{TF1} < \text{F1}) \\
 & \text{or } (\text{TF2} < \text{F4} \text{ and } \text{TF1} > \text{F2}) \\
 & \text{or } (\text{TF2} \geq \text{F4} \text{ and } \text{TF1} > \text{F3})
 \end{aligned}$$

Icing Test: An icing event occurs when ice collects on a sensor and degrades its performance. Icing events are characterized by the simultaneous measurements of near-zero standard deviation of wind direction, non-zero wind speed, and near- or below-freezing temperatures. Wind speed, wind speed standard deviation, wind direction, and wind direction standard deviation data values are flagged if the wind direction standard deviation (CF1) is less than or equal to Factor 1 (F1), the wind speed (TF1) is greater than Factor 2 (F2), and the temperature (CF2) is less than Factor 3 (F3). To exit an icing event, the wind direction standard deviation must be greater than Factor 4.

$$\text{CF1} \leq \text{F1} \text{ and } \text{TF1} > \text{F2} \text{ and } \text{CF2} < \text{F3}$$

CompareSensors Test: Where primary and redundant sensors are used, it is possible to determine when one of the sensors is not performing properly. For anemometers, poor performance is characterized by low data values. Therefore, if one sensor of the pair reports values significantly below the other, the low values are flagged. At low wind speeds (Test Fields 1 and 2 less than or equal to Factor 3) wind speed data are flagged if the absolute difference between the two wind speeds is greater than Factor 1. At high wind speeds (Test Fields 1 or 2 greater than Factor 3) wind speed data are flagged if the absolute value of the ratio of the two wind speeds is greater is greater than Factor 2.

$$\begin{aligned}
 & [\text{TF1} \leq \text{F3} \text{ and } \text{TF2} \leq \text{F3} \text{ and } \text{abs}(\text{TF1} - \text{TF2}) > \text{F1}] \\
 & \text{or } [(\text{TF1} > \text{F3} \text{ or } \text{TF2} > \text{F3}) \text{ and } (\text{abs}(1 - \text{TF1} / \text{TF2}) > \text{F2} \text{ or } \text{abs}(1 - \text{TF2} / \text{TF1}) > \text{F2})]
 \end{aligned}$$

Sensor Statistics

A summary of the results of the data collection and filtering are given in the Sensor Performance Report which is included in APPENDIX A. The following categories of information, tabulated for each sensor, are included in that report.

Expected Data Points: the total number of sample intervals between the start and end dates (inclusive).

Actual Data Points: the total number of data points recorded between the start and end dates.

% Data Recovered: the ratio of actual and expected data points (this is the *gross data recovered percentage*).

Hours Out of Range: total number of hours for which data were flagged according to MinMax and MinMaxT tests. These tests flag data which fall outside of an expected range.

Hours of Icing: total number of hours for which data were flagged according to Icing tests. This test uses the standard deviation of wind direction, air temperature, and wind speed to determine when sensor icing has occurred.

Hours of Fault: total number of hours for which data were flagged according to CompareSensors tests. These tests compare two sensors (e.g. primary and redundant anemometers installed at the same height) and flag data points where one sensor differs significantly from the other.

% Data Good: the filter results are subtracted from the gross data recovery percentage to yield the *net data recovered percentage*.

APPENDIX A - Sensor Performance Report

Test Definitions

Test Order	TestField1	TestField 2	TestField 3	CalcField 1	CalcField 2	Calc Field3	Test Type	Factor 1	Factor 2	Factor 3	Factor 4
1	Anem50aMS					MinMax	0	90			1
2	Anem50bMS					MinMax	0	90			2
3	Anem40aMS					MinMax	0	90			3
4	Anem40bMS					MinMax	0	90			4
5	Anem50yMS					MinMax	0	90			5
6	Anem40yMS					MinMax	0	90			6
7	Vane50aDEG					MinMax	0	359.9			7
8	Vane40aDEG					MinMax	0	359.9			8
9	Etemp2aDEGF					MinMax	-30	60			9
10	Batt2aVDC					MinMax	10.5	15			10
11	Turb50zNONE					MinMax	0	2			11
12	Turb40zNONE					MinMax	0	2			12
13	AnemSD50aMS					MinMax	0	4			13
14	AnemSD50bMS					MinMax	0	4			14
15	AnemSD40aMS					MinMax	0	4			15
16	AnemSD40bMS					MinMax	0	4			16
17	AnemSD50yMS					MinMax	0	4			17
18	AnemSD40yMS					MinMax	0	4			18
21	EtempSD2aDEGF					MinMax	-30	60			21
22	BattSD2aVDC					MinMax	0	5			22
200	VaneSD50aDEG	Anem50yMS				MinMax	0	100	100	10	200
201	VaneSD40aDEG	Anem40yMS				MinMax	0	100	100	10	201
300	Anem50aMS	AnemSD50aMS	Vane50aDEG	VaneSD50aDEG	Etemp2aDEGF	Icing	0.5	1	2	4	300
301	Anem50bMS	AnemSD50bMS	Vane50aDEG	VaneSD50aDEG	Etemp2aDEGF	Icing	0.5	1	2	4	301
302	Anem40aMS	AnemSD40aMS	Vane40aDEG	VaneSD40aDEG	Etemp2aDEGF	Icing	0.5	1	2	4	302
303	Anem40bMS	AnemSD40bMS	Vane40aDEG	VaneSD40aDEG	Etemp2aDEGF	Icing	0.5	1	2	4	303
304	Anem50yMS	AnemSD50yMS	Vane50aDEG	VaneSD50aDEG	Etemp2aDEGF	Icing	0.5	1	2	4	304
305	Anem40yMS	AnemSD40yMS	Vane40aDEG	VaneSD40aDEG	Etemp2aDEGF	Icing	0.5	1	2	4	305
400	Anem50aMS	Anem50bMS				Compare Sensors	1	0.25	3	0	400
401	Anem40aMS	Anem40bMS				Compare Sensors	1	0.25	3	0	401

Sensor Statistics

Sensor	Expected Data Points	Actual Data Points	% Data Recovered	Hours Out of Range	Hours of Icing	Hours of Fault	% Data Good
Anem50aMS	12817	12817	100	0.833	151.333	49.667	90.552
Anem50bMS	12817	12817	100	1.667	151.667	42.833	90.817
Anem40aMS	12817	12817	100	0.333	187.5	59.833	88.406
Anem40bMS	12817	12817	100	1.5	191.833	39.667	89.093
Vane50aDEG	12817	12817	100	0	151.667	0	92.9
Vane40aDEG	12817	12817	100	0	191.833	0	91.02
Etemp2aDEGF	12817	12817	100	0	0	0	100
Anem50yMS	12817	12817	100	0	151.333	0	92.916
Anem40yMS	12817	12817	100	0	187.5	0	91.223
Total	115353	115353	100	4.333	1364.667	192	91.881

APPENDIX B - Plot Data

Wind Speed Distribution Data

Wind Speed [m/s]	Time [%]
0.5	0.54
1.5	1.39
2.5	3.11
3.5	5.59
4.5	9.53
5.5	11.26
6.5	11.92
7.5	11.76
8.5	10.97
9.5	8.83
10.5	6.6
11.5	5.48
12.5	3.77
13.5	3.15
14.5	1.92
15.5	1.63
16.5	1.24
17.5	0.84
18.5	0.27
19.5	0.09
20.5	0.05
21.5	0.04
22.5	0
23.5	0
24.5	0

Diurnal Average Wind Speed Data

Hour of day	Wind Speed [m/s]
-------------	------------------

0.5	7.94
1.5	7.95
2.5	7.74
3.5	7.65
4.5	7.53
5.5	7.59
6.5	7.54
7.5	7.58
8.5	7.51
9.5	7.88
10.5	8.18
11.5	8.31
12.5	8.34
13.5	8.17
14.5	8
15.5	7.98
16.5	7.92
17.5	8.12
18.5	8.3
19.5	8.32
20.5	8.21
21.5	8.13
22.5	7.94
23.5	7.91

Monthly Average Wind Speed Data

Month	50 m Mean Wind Speed
--------------	---------------------------------

	[m/s]
December 2007	8.75
January 2008	7.38
February 2008	7.69

Wind Rose Data

Wind Direction	Mean Wind Speed [m/s]	Percent of Time [%]
N	6.86	9.63
NNE	6.55	7.3
NE	5.46	3.29
ENE	6.58	2.5
E	10.15	2.25
ESE	9.87	2.21
SE	6.89	1.98
SSE	6.5	1.19
S	7.04	1.91
SSW	8.36	4.04
SW	9.57	11.19
WSW	7.72	7.45
W	6.6	5.93
WNW	7.81	7.6
NW	8.69	13.5
NNW	8.51	18.02