

WIND DATA REPORT

FALMOUTH, MA

Sep 1st 2004 to Nov 30th 2004.

Prepared for

Massachusetts Technology Collaborative
75 North Drive
Westborough, MA 01581

By

James F. Manwell
Anthony L. Rogers
Anthony F. Ellis
Ashwin Gambhir

January 10, 2005

NOTICE AND ACKNOWLEDGEMENTS

This report was prepared by the Renewable Energy Research Laboratory (RERL) at the University of Massachusetts, Amherst in the course of performing work sponsored by the Renewable Energy Trust (RET), as administered by the Massachusetts Technology Collaborative (MTC), pursuant to work order number 05-1. The opinions expressed in this report do not necessarily reflect those of MTC or the Commonwealth of Massachusetts, and reference to any specific product, service, process, or method does not constitute an implied or expressed recommendation or endorsement of it.

Further, MTC, the Commonwealth of Massachusetts, and RERL make no warranties or representations, expressed or implied, as to the fitness for particular purpose or merchantability of any product, apparatus, or service, or the usefulness, completeness, or accuracy of any processes, methods or other information contained, described, disclosed, or referred to in this report. MTC, the Commonwealth of Massachusetts, and the contractor make no representation that the use of any product, apparatus, process, method, or other information will not infringe privately owned rights and will assume no liability for any loss, injury, or damage directly or indirectly resulting from, or occurring in connection with, the use of information contained, described, disclosed, or referred to in this report.

TABLE OF CONTENTS

Table of Contents	1
Table of Figures	1
Executive Summary	2
SECTION 1 - Station Location.....	3
SECTION 2 - Instrumentation and Equipment.....	3
SECTION 3 - Data Collection and Maintenance.....	4
SECTION 4 - Significant Meteorological Events	5
SECTION 5 - Data Recovery and Validation.....	5
Test Definitions.....	5
Sensor Statistics	6
SECTION 6 - Data Summary	7
SECTION 7 - Graphs.....	9
Wind Speed Time Series.....	9
Wind Speed Distributions	10
Monthly Average Wind Speeds	10
Diurnal Average Wind Speeds.....	11
Turbulence Intensities.....	11
Wind Roses	12
APPENDIX A - Sensor Performance Report	13
Test Definitions.....	13
Sensor Statistics	14
APPENDIX B - Plot Data.....	16
Wind Speed Distribution Data	16
Monthly Average Wind Speed Data	17
Diurnal Average Wind Speed Data.....	18
Wind Rose Data	19

TABLE OF FIGURES

Figure 1 - Site location at Falmouth site.....	3
Figure 2- Wind Speed Time Series, Sep 1, 2004 to Nov 30, 2004.....	9
Figure 3 - Wind Speed Distribution, Sep 1, 2004 to Nov 30, 2004.....	10
Figure 4 - Monthly average wind speeds, May 2004 to Nov 2004.....	10
Figure 5 - Diurnal Wind Speed, Sep 1, 2004 to Nov 30, 2004.....	11
Figure 6 - Turbulence Intensity vs. Wind Speed, Sep 1, 2004 to Nov 30, 2004.....	11
Figure 7 – Wind Rose, Sep 1, 2004 to Nov 30, 2004.....	12

EXECUTIVE SUMMARY

All the work presented in this Wind Data Report including installation and decommissioning of the meteorological tower and instrumentation, and the data analysis and reporting was performed by the Renewable Energy Research Laboratory (RERL) at the University of Massachusetts, Amherst.

Wind monitoring at Falmouth commenced on April 30th, 2004 and the station is in continuous operation to this day. Wind speed and direction monitoring are being done at three heights 39m, 30m and 10m. This report is for the quarter from September 1st 2004 through November 30th 2004. During the period covered by this report, September 2004 through November 2004, the mean recorded wind speed at 39 meters was 5.42 m/s (12.19mph) *; the prevailing wind direction at 39 meters was from the north. The mean monthly wind speed increases each month from September through to November. The gross data recovery percentage (the actual percentage of expected data received) was 100 % and the net data recovery percentage (the percentage of expected data which passed all of the quality assurance tests) was 94.405%. The net data recovery percentage is slightly low primarily due to the failed vane at the 30 m level.

Additional information about interpreting the data presented in this report can be found in the Fact Sheet, "Interpreting Your Wind Resource Data," produced by RERL and the Massachusetts Technology Collaborative (MTC). This document is found through the RERL website:

http://www.ceere.org/rerl/about_wind/RERL_Fact_Sheet_6_Wind_resource_interpretation.pdf

* 1 m/s = 2.25 mph.

SECTION 1 - Station Location

The site is located on the Town Water Treatment Plant in Falmouth, MA. The tower base is located at 41.606° N, and 70.621° W (NAD 27).




Figure 1 - Site location at Falmouth site.

Source: www.topozone.com.

SECTION 2 - Instrumentation and Equipment

Wind monitoring equipment is mounted on a standard NRG 40 m tall, 6 in diameter tilt-up guyed tower. Wind vanes and anemometers are located at three heights on the tower: 10 m, 30 m, and 39 m. Redundant anemometers exist at 30 m and 39 m.

Additional equipment and models:

- NRG model Symphonie Cellogger
- 5 – #40 Anemometers, standard calibration (Slope - 0.765 m/s, Offset – 0.350 m/s)
- 3 - #200P Wind direction vanes

- Lightning rod and grounding cable
- NRG 11S temperature Sensor

The data from the Symphonie logger is mailed to the University of Massachusetts, Amherst on a regular basis. The logger samples wind speed and direction once every two seconds. These are then combined into 10-minute averages, and along with the standard deviation for those 10-minute periods, are put into a binary file. These binary files are converted to ASCII text files using the NRG software BaseStation®. These text files are then imported into a database software program where they are subjected to QA tests prior to using the data.

SECTION 3- Data Collection and Maintenance

The following maintenance/equipment problems occurred during the report period, and the following corrective actions taken:

- The vane at the 30 m level is dead as can be seen from the near constant value of the standard deviation value for that sensor.
- No data were missing (i.e. the logger reported values for every 10-minute timestamp).
- No maintenance operations were performed during this quarter.

Data Statistics Summary

Date	Mean Wind Speed	Max Wind Speed	Turbulence Intensity	Prevailing Wind Direction	Mean Wind Speed	Max Wind Speed	Turbulence Intensity	Mean Wind Speed	Max Wind Speed	Prevailing Wind Direction	Turbulence Intensity
Heights, units	39 m, [m/s]	39 m, [m/s]	39 m, []	39 m, []	30 m, [m/s]	30 m, [m/s]	30 m, []	10 m, [m/s]	10 m, [m/s]	10 m, []	10 m, []
Sep-04	5.01	15.37	0.18	SW	4.48	14.52	0.21	3.1	12.25	SW	0.32
Oct-04	5.51	11.8	0.18	NE	4.98	11.06	0.2	3.68	10	NNE	0.27
Nov-04	5.75	16.33	0.19	N	5.14	15.19	0.22	3.75	12.13	NNW	0.29
Sep- Nov 04	5.36	16.33	0.18	N	4.83	15.19	0.21	3.52	12.25	N	0.29

No measurement of wind speed can be perfectly accurate. Errors occur due to anemometer manufacturing variability, anemometer calibration errors, the response of anemometers to turbulence, and vertical airflow and due to airflows caused by the anemometer mounting system. Every effort is made to reduce the sources of these errors. Nevertheless, the values reported in this report have an expected uncertainty of about $\pm 2\%$ or ± 0.2 m/s.

SECTION 4- Significant Meteorological Events

There are no major wind events shown in the wind speed time series for this quarter of September to November 2004.

During the fall of 2004 several hurricanes affected weather on the east coast of the US, though none of these storms produced abnormally strong winds in eastern Massachusetts. The winds of Hurricanes Karl and Jeanne did produce high surf along the Massachusetts coast, but the storm was too far from shore for their winds to be felt.

Source: <http://www.erh.noaa.gov/box/MonthlyClimate2.shtml>

SECTION 5 - Data Recovery and Validation

All raw wind data are subjected to a series of tests and filters to weed out data that are faulty or corrupted. Definitions of these quality assurance (QA) controls are given below under Test Definitions and Sensor Statistics. These control filters were designed to automate the quality control process and used many of the previous hand-worked data sets made at the RERL to affect a suitable emulation. The gross percentage of data recovered (ratio of the number of raw data points received to data points expected) and net percentage (ratio of raw data points which passed all QA control tests to data points expected) are shown below.

Gross Data Recovered [%]	100
Net Data Recovered [%]	94.405

Test Definitions

All raw data were subjected to a series of validation tests, as described below. The sensors tested and the parameters specific to each sensor are given in the Sensor Performance Report, which is included in APPENDIX A. Data that were flagged as invalid were not included in the statistics presented in this report.

MinMax Test: All sensors are expected to report data values within a range specified by the sensor and logger manufacturers. If a value falls outside this range, it is flagged as invalid. A data value from the sensor listed in Test Field 1 (TF1) is flagged if it is less than Factor 1 (F1) or greater than Factor 2. This test has been applied to the following sensors (as applicable): wind speed, wind speed standard deviation, wind direction, temperature, and solar insolation.

$$F1 > TF1 > F2$$

MinMaxT Test: This is a MinMax test for wind direction standard deviation with different ranges applied for high and low wind speeds. A wind direction standard deviation data value (TF1) is flagged either if it is less than Factor 1, if the wind speed (TF2) is less than Factor 4 and the wind direction standard deviation is greater than Factor 2, or if the wind speed is greater than or equal to Factor 4 and the wind direction standard deviation is greater than Factor 3.

$$\begin{aligned} & (TF1 < F1) \\ & \text{or } (TF2 < F4 \text{ and } TF1 > F2) \\ & \text{or } (TF2 \geq F4 \text{ and } TF1 > F3) \end{aligned}$$

Icing Test: An icing event occurs when ice collects on a sensor and degrades its performance. Icing events are characterized by the simultaneous measurements of near-zero standard deviation of wind direction, non-zero wind speed, and near- or below-freezing temperatures. Wind speed, wind speed standard deviation, wind direction, and wind direction standard deviation data values are flagged if the wind direction standard deviation (CF1) is less than or equal to Factor 1 (F1), the wind speed (TF1) is greater than Factor 2 (F2), and the temperature (CF2) is less than Factor 3 (F3). To exit an icing event, the wind direction standard deviation must be greater than Factor 4 (F4).

$$CF1 \leq F1 \text{ and } TF1 > F2 \text{ and } CF2 < F3$$

CompareSensors Test: Where primary and redundant sensors are used, it is possible to determine when one of the sensors is not performing properly. For anemometers, poor performance is characterized by low data values. Therefore, if one sensor of the pair reports values significantly below the other, the low values are flagged. At low wind speeds (Test Fields 1 and 2 less than or equal to Factor 3) wind speed data are flagged if the absolute difference between the two wind speeds is greater than Factor 1. At high wind speeds (Test Fields 1 or 2 greater than Factor 3) wind speed data are flagged if the absolute value of the ratio of the two wind speeds is greater is greater than Factor 2.

$$\begin{aligned} & [TF1 \leq F3 \text{ and } TF2 \leq F3 \text{ and } \text{abs}(TF1 - TF2) > F1] \\ & \text{or } [(TF1 > F3 \text{ or } TF2 > F3) \text{ and } (\text{abs}(1 - TF1 / TF2) > F2 \text{ or } \text{abs}(1 - TF2 / TF1) > F2)] \end{aligned}$$

Sensor Statistics

Expected Data Points: the total number of sample intervals between the start and end dates (inclusive).

Actual Data Points: the total number of data points recorded between the start and end dates.

% Data Recovered: the ratio of actual and expected data points (this is the *gross data recovered percentage*).

Hours Out of Range: total number of hours for which data were flagged according to MinMax and MinMaxT tests. These tests flag data that fall outside of an expected range.

Hours of Icing: total number of hours for which data were flagged according to Icing tests. This test uses the standard deviation of wind direction, air temperature, and wind speed to determine when sensor icing has occurred.

Hours of Fault: total number of hours for which data were flagged according to CompareSensors tests. These tests compare two sensors (e.g. primary and redundant anemometers installed at the same height) and flag data points where one sensor differs significantly from the other.

% Data Good: the filter results are subtracted from the gross data recovery percentage to yield the *net data recovered percentage*.

SECTION 6 - Data Summary

This report contains several types of wind data graphs. Unless otherwise noted, each graph represents data from 1 quarter (3 months). The following graphs are included:

- Time Series – 10-minute average wind speeds are plotted against time. The wind speed time series is shown in Figure 2.
- Wind Speed Distribution – A histogram plot giving the percentage of time that the wind is at a given wind speed. The plot shows a peak between 4 and 5 m/s. The wind speed distribution is shown in Figure 3.
- Monthly Average – This graph shows the trends in the mean monthly wind speed from May 2004 - Nov 2004. The mean wind speed for all three months for this quarter is above 5m/s. The monthly average wind speed plot is shown in Figure 4.
- Diurnal – A plot of the average wind speed for each hour of the day. The hourly mean wind speed varied between 5 and 6 m/s. This graph shows a peak wind speed between 11 AM and 2 PM. The diurnal variation plot is shown in Figure 5.
- Turbulence Intensity – A plot of turbulence intensity as a function of wind speed. Turbulence Intensity is calculated as the standard deviation of the wind speed divided by the wind speed and is a measure of the gustiness of a wind resource. Lower turbulence results in lower mechanical loads on a wind turbine. The turbulence intensity flattens out after 7 m/s. The turbulence intensity plot is shown in Figure 6.
- Wind Rose – A plot, by compass direction showing the percentage of time that the wind comes from a given direction and the average wind speed in that

direction. This quarter's wind rose shows the prevailing wind direction at the 39 m height to be from the north. The wind rose plot is shown in Figure 7.

SECTION 7- Graphs

Data for the wind speed histograms, monthly and diurnal average plots, and wind roses are included in APPENDIX B.

Wind Speed Time Series




Figure 2- Wind Speed Time Series, September 2004 – November 2004

Wind Speed Distributions




Figure 3 - Wind Speed Distribution, September 2004 – November 2004

Monthly Average Wind Speeds





Figure 4 - Monthly average wind speeds, May 2004 – November 2004.

Diurnal Average Wind Speeds

Falmouth Diurnal Average Wind Speed, 39 m




Plot by DQMS3 - dqms@dqms.com

Figure 5 - Diurnal Wind Speed, September 2004 – November 2004

Turbulence Intensities

Falmouth Turbulence Intensity, 39 m




Plot by DQMS3 - dqms@dqms.com

Figure 6 - Turbulence Intensity vs. Wind Speed, September 2004 – November 2004

Wind Rose

Falmouth wind rose [39 m]



Plot by DQMS3 - dqms@dqms.com

Figure 7 – Wind Rose, September 2004 – November 2004

APPENDIX A - Sensor Performance Report

Test Definitions

TestOrder	TestField1	TestField2	TestField3	CalcField1	CalcField2	TestType	Factor1	Factor2	Factor3	Factor4
1						TimeTest Insert	0	0	0	0
4	Etmp2aDEGC					MinMax	-30	60	0	0
5	EtmpSD2aDEGC					MinMax	-30	60	0	0
10	Anem10aMS					MinMax	0	90	0	0
11	Anem30aMS					MinMax	0	90	0	0
12	Anem30bMS					MinMax	0	90	0	0
13	Anem39aMS					MinMax	0	90	0	0
14	Anem39bMS					MinMax	0	90	0	0
15	Anem30yMS					MinMax	0	90	0	0
16	Anem39yMS					MinMax	0	90	0	0
20	AnemSD10aMS					MinMax	0	4	0	0
21	AnemSD30aMS					MinMax	0	4	0	0
22	AnemSD30bMS					MinMax	0	4	0	0
23	AnemSD39aMS					MinMax	0	4	0	0
24	AnemSD39bMS					MinMax	0	4	0	0
30	Vane10aDEG					MinMax	0	359.9	0	0
31	Vane30aDEG					MinMax	0	359.9	0	0
32	Vane39aDEG					MinMax	0	359.9	0	0
50	Turb10zNONE					MinMax	0	2	0	0
51	Turb30zNONE					MinMax	0	2	0	0
52	Turb39zNONE					MinMax	0	2	0	0
60	Wshr0zNONE					MinMax	-100	100	0	0
200	VaneSD10aDEG	Anem10aMS				MinMaxT	0	100	100	10
201	VaneSD30aDEG	Anem30yMS				MinMaxT	0	100	100	10
202	VaneSD39aDEG	Anem39yMS				MinMaxT	0	100	100	10
300	Anem10aMS	AnemSD10aMS	Vane10aDEG	VaneSD10aDEG	Etmp2aDEGC	Icing	0.5	1	2	0
301	Anem30aMS	AnemSD30aMS	Vane30aDEG	VaneSD10aDEG	Etmp2aDEGC	Icing	0.5	1	2	0
302	Anem30bMS	AnemSD30bMS	Vane30aDEG	VaneSD30aDEG	Etmp2aDEGC	Icing	0.5	1	2	0
303	Anem39aMS	AnemSD39aMS	Vane39aDEG	VaneSD39aDEG	Etmp2aDEGC	Icing	0.5	1	2	0
304	Anem39bMS	AnemSD39bMS	Vane39aDEG	VaneSD39aDEG	Etmp2aDEGC	Icing	0.5	1	2	0
400	Anem30aMS	Anem30bMS				CompareSensors	1	0.25	3	0
401	Anem39aMS	Anem39bMS				CompareSensors	1	0.25	3	0
500	Amax10aMS					MinMax	0	90	0	0
501	Amin10aMS					MinMax	0	90	0	0
502	Amax30aMS					MinMax	0	90	0	0
503	Amin30aMS					MinMax	0	90	0	0
504	Amax30bMS					MinMax	0	90	0	0
505	Amin30bMS					MinMax	0	90	0	0

506	Amax39aMS				MinMax	0	90	0	0
507	Amin39aMS				MinMax	0	90	0	0
508	Amax39bMS				MinMax	0	90	0	0
509	Amin39bMS				MinMax	0	90	0	0
540	Vmax10aDEG				MinMax	0	359.9	0	0
541	Vmin10aDEG				MinMax	0	359.9	0	0
542	Vmax30aDEG				MinMax	0	359.9	0	0
543	Vmin30aDEG				MinMax	0	359.9	0	0
544	Vane39aDEG				MinMax	0	359.9	0	0
560	Emax2aDEGC				MinMax	-30	60	0	0
561	Emin2aDEGC				MinMax	-30	60	0	0
562	Vmax39aDEG				MinMax	0	360	0	0
563	Vmin39aDEG				MinMax	0	360	0	0
564	Pwr10zWMC				MinMax	0	500	0	0
565	Pwr30zWMC				MinMax	0	500	0	0
566	Pwr39zWMC				MinMax	0	500	0	0

Sensor Statistics

Sensor	Expected Data Points	Actual Data Points	% Data Recovered	Hours Out of Range	Hours of Icing	Hours of Fault	% Data Good
Anem39aMS	12961	12961	100	0	0	1.5	99.931
AnemSD39aMS	12961	12961	100	0	0	1.5	99.931
Amax39aMS	12961	12961	100	0	0	0	100
Amin39aMS	12961	12961	100	0	0	0	100
Anem39bMS	12961	12961	100	0.167	0	8.5	99.599
AnemSD39bMS	12961	12961	100	0.167	0	8.5	99.599
Amax39bMS	12961	12961	100	0	0	0	100
Amin39bMS	12961	12961	100	0	0	0	100
Anem30aMS	12961	12961	100	0	0	1	99.954
AnemSD30aMS	12961	12961	100	0	0	1	99.954
Amax30aMS	12961	12961	100	0	0	0	100
Amin30aMS	12961	12961	100	0	0	0	100
Anem30bMS	12961	12961	100	0	0	4	99.815
AnemSD30bMS	12961	12961	100	0	0	4	99.815
Amax30bMS	12961	12961	100	0	0	0	100
Amin30bMS	12961	12961	100	0	0	0	100
Anem10aMS	12961	12961	100	0	0	0	100
AnemSD10aMS	12961	12961	100	0	0	0	100
Amax10aMS	12961	12961	100	0	0	0	100
Amin10aMS	12961	12961	100	0	0	0	100
Vane39aDEG	12961	12961	100	0	0	0	100
VaneSD39aDEG	12961	12961	100	0	0	0	100
Vmax39aDEG	12961	12961	100	0	0	0	100
Vmin39aDEG	12961	12961	100	0	0	0	100
Vane30aDEG	12961	12961	100	8.167	0	2152	0
VaneSD30aDEG	12961	12961	100	8.167	0	2152	0

Vmax30aDEG	12961	12961	100	0	0	0	100
Vmin30aDEG	12961	12961	100	0	0	0	100
Vane10aDEG	12961	12961	100	0.167	0	0	99.992
VaneSD10aDEG	12961	12961	100	0.167	0	0	99.992
Vmax10aDEG	12961	12961	100	0	0	0	100
Vmin10aDEG	12961	12961	100	0	0	0	100
Etmp2aDEGC	12961	12961	100	0	0	0	100
EtmpSD2aDEGC	12961	12961	100	0	0	0	100
Emax2aDEGC	12961	12961	100	0	0	0	100
Emin2aDEGC	12961	12961	100	0	0	0	100
Total	466596	466596	100	17	0	4334	94.405

APPENDIX B - Plot Data

Wind Speed Distribution Data

Bin Center Wind Speed [m/s]	Percent of Time [%]
0.5	1.36
1.5	3.52
2.5	9
3.5	16.12
4.5	19.76
5.5	17.16
6.5	11
7.5	7.55
8.5	6.01
9.5	4.05
10.5	2.51
11.5	0.95
12.5	0.44
13.5	0.27
14.5	0.16
15.5	0.12
16.5	0.02
17.5	0
18.5	0
19.5	0
20.5	0
21.5	0
22.5	0
23.5	0
24.5	0

Table 1 - Wind Speed Distribution, Sep 2004- Nov 2004

Monthly Average Wind Speed Data

Date	10 min Mean [m/s]
May 04	4.89
June 04	5.00
July 04	4.62
Aug 04	5.04
Sep 04	5.01
Oct 04	5.51
Nov 04	5.75

Table 2 - Wind Speed Averages

Diurnal Average Wind Speed Data

Hour of Day	Average Wind Speed [m/s]
0	5.33
1	5.29
2	5.26
3	5.29
4	5.18
5	5.21
6	5.04
7	4.98
8	5.1
9	5.36
10	5.5
11	5.65
12	5.66
13	5.8
14	5.73
15	5.3
16	5.21
17	5.26
18	5.4
19	5.52
20	5.47
21	5.42
22	5.37
23	5.35

Table 3 - Diurnal Average Wind Speeds, Sep 2004- Nov 2004

Wind Rose Data

Direction	Percent Time [%], 39 m	Mean Wind Speed [m/s], 39 m
N	12.04	5.24
NNE	6.65	6.22
NE	9.15	6.44
ENE	4.71	4.93
E	2.18	3.74
ESE	4.82	4.79
SE	4.77	4.02
SSE	6.24	4.5
S	4.29	5.66
SSW	4.75	5.67
SW	11.69	5.63
WSW	6.53	5.66
W	5.67	5.73
WNW	3.92	5.26
NW	4.61	4.76
NNW	7.97	5.26

Table 4 - Wind Rose, Time Percentage and Mean Wind Speed by Direction, Sep 2004- Nov 2004