



Renewable Energy Research Laboratory

Department of Mechanical and Industrial Engineering



The Hull Wind II Project

James F. Manwell

Director, RERL


May 30, 2006

University of Massachusetts





Hull Locator Map





Background

- Hull has had a long history of using wind energy
- Hull Wind I, 660 kW, 47 m turbine was installed in 2001
- Planning for Hull Wind II began shortly thereafter





Hull Wind II

- 1.8 MW Vestas V80 wind turbine and tower
- Tower height: 60 meters
- Turbine blade rotor diameter: 80 meters
 - Blade length: 40 meters
- Tip of blade to ground: 100 meters
- Turbine placed on town landfill.
 - Height: 60 ft (~20 m)



Hull Wind II

- Foundation built on pilings driven through 60' closed landfill and 20' into bedrock
- First wind turbine installed on a landfill in US
- Owner is Hull Municipal Lighting Plant, a publicly owned municipal utility
- 100% of electricity will be sold at retail to HMLP customers
- Distribution lines owned by HMLP



Hull Wind II: Important Dates

- Hull Wind I commissioned, 12/2001
- Discussions begin for second turbine, 2/2002
- Poll supports second turbine, 95%, 10/2002
- Possible sites considered, 2003-2004
- Top of closed landfill chosen as site, 10/2004
- Permitting process begun, 12/2004
- Turbine ordered, 4/2005
- Foundation constructed, 12/2005
- Installation completed, 4/2006
- Turbine on line, 5/2006



Hull Wind II Site Options

*Pemberton/
Windmill Point*

Stony Point

*Mariners'
Park*


Landfill





Site Assessment

- Wind maps
- Economics
- Data collection
- Public input
- Visualizations





Hull Wind I and Visualization of HWII at Windmill Point (1)



View from Allerton



Hull I and Visualization of HW II at Windmill Point (2)



*GE 1.5SL on
65 m tower*

Hull Wind I



Visualization: Mariner's Park



GE 1.5SL Wind Turbine

View from Ft. Revere

University of Massachusetts





Visualization at Landfill





Photo Simulation of Hull 2 Wind Power Project

About the Project:	About the Photo:
Owner: Hull Municipal Light	Viewpoint: George Washington Blvd, at the bridge over Weir River
Project site: Town Landfill	Angle of View: 53 degrees
Turbine: Vestas V80, 1.8 MW	Location: 42.25° N, 70.86° W
Diameter: 263 feet (80 m)	Apparent size and location of the turbine from this viewpoint is determined geometrically using RETool WindFarm software.
Hub height: 197 feet (60 m)	
Location: 42.26° N, 70.85° W	

Renewable Energy Research Laboratory
Department of Mechanical & Industrial Engineering
University of Massachusetts
160 Governor's Drive
Amherst, MA 01003-9265
413-545-4359
www.coern.org/rel
rel@rel.org



View from Weir River bridge

University of Massachusetts





Wind Data Collection


- SODAR at Landfill
 - Uses sound to study wind
- SODAR used to investigate wind shear and provide basis for correlations





Wind Data/Turbine Power Analysis


- Short term wind speed and wind shear
- Correlations with long term sites (“MCP”)
- Capacity factor should be similar to Hull Wind I’s (approximately 0.27)
- Will produce ~ 9% of Hull’s electricity



Results from MCP	
Long-term Data used: Thompson Island Nov 26 2004 to Nov 25 2005 Avg Speed: 5.98 m/s	
Concurrent Data: Oct 17 to Nov 17 2005 Increased Sodar wind speeds by 0.5 m/s prior to MCP	
To reflect long-term Logan data, Mean Wind Speed increased by factor: 1.026	
Hull 2 Predictions (at 60m)	
Avg Speed:	7.03 m/s
k	2.52
c	7.92



Hull's Electricity Use and Contributions from its First Two Wind Turbines



- Fraction from wind approximately 12%




Environmental Impacts

- Close proximity to houses primary concern
- Common issues, such as noise and avian impacts, of secondary importance to Hull residents
- Certain percentage of REC income to be given to Weir River Association
- HMLP agreed to a voluntary 1 year bird study-performed by Mass Audubon
- Objections from neighboring town (Hingham), based on visual, found to be w/out merit



Foundation Design

- Turbine bolted to reinforced concrete pad (20' x 20' x 6') on top of landfill
- Pad connected to bedrock via long, hollow anchor bolts, drilled and grouted in place






Foundation Design (2)

- Piles driven through landfill to bedrock provide conduit for anchor bolts

Tower connection bolts, attached to embedment plate in pad





Economics: Costs

- Turbine: \$1,800,000
- Foundation: \$850,000
- Other: \$350,000
- Total: \$3,000,000
 - Cost per kW, installed: \$1,666
- Annual recurring costs:
 - O&M: \$25,000/yr
 - Insurance: \$16,000/yr



Economics: Benefits

- Energy: 4,250,000 kWh/yr
- Value of displaced power: \$0.10/kWh
- Simple Payback: 7.5 yrs
 - Less than 5 yrs, when RECs considered
- Cost of Energy: \$0.045-0.056/kWh
- Net annual savings to Town:
\$250,000 - \$425,000
(depends on assumptions regarding financial factors,
inflation, incentives such as REC's, REPI etc.)



Renewable Energy Research Laboratory

Department of Mechanical and Industrial Engineering

Blades Arriving by Ship





Nacelle Arriving in Quincy





Nacelle Being Unloaded





Renewable Energy Research Laboratory

Department of Mechanical and Industrial Engineering

Blades on Site





Renewable Energy Research Laboratory

Department of Mechanical and Industrial Engineering

Pile Driving for Foundation





Foundation Pilings





Renewable Energy Research Laboratory

Department of Mechanical and Industrial Engineering

Completed Turbine



University of Massachusetts





Keys to Success

- Qualified and experienced partners
 - Municipal electric company ideal host
- Adequate wind resource
 - Sufficient height above ground
- Guaranteed value of energy
- Clear public benefit
 - Non-restrictive regulations
- Opportunities for meaningful public input
- Reputable and responsive turbine supplier
- Contract details



Next Steps

- Monitor initial operation of Hull II
- Formal dedication this summer
- Install small turbine (Southwest 1.8 kW) at Weir River Assoc. visitors center
- Pursue development of Hull Offshore Wind Energy Project

