

# WIND DATA REPORT

## Swan's Island, ME

September 1, 2008 – November 30, 2008

Prepared for

US Department of Energy

by

Daniel T. Grip  
Utama Abdulwahid  
James F. Manwell  
Anthony F. Ellis

January 18, 2009

Report template version 3.1.1

---

---

Renewable Energy Research Laboratory  
University of Massachusetts, Amherst  
160 Governors Drive, Amherst, MA 01003

[www.ceere.org/rerl](http://www.ceere.org/rerl) • (413) 545-4359 • [rerl@ecs.umass.edu](mailto:rerl@ecs.umass.edu)



## **NOTICE AND ACKNOWLEDGEMENTS**

This report was prepared by the Renewable Energy Research Laboratory (RERL) at the University of Massachusetts, Amherst in the course of performing work sponsored by the US Department of Energy. The opinions expressed in this report do not necessarily reflect those of the US DOE and reference to any specific product, service, process, or method does not constitute an implied or expressed recommendation or endorsement of it.

Further, the US DOE, and RERL make no warranties or representations, expressed or implied, as to the fitness for particular purpose or merchantability of any product, apparatus, or service, or the usefulness, completeness, or accuracy of any processes, methods or other information contained, described, disclosed, or referred to in this report. The US DOE and RERL make no representation that the use of any product, apparatus, process, method, or other information will not infringe privately owned rights and will assume no liability for any loss, injury, or damage directly or indirectly resulting from, or occurring in connection with, the use of information contained, described, disclosed, or referred to in this report.

# TABLE OF CONTENTS

Notice and Acknowledgements .....	1
Table of Contents .....	2
Table of Figures .....	3
Executive Summary .....	4
SECTION 1 - Station Location .....	5
SECTION 2 - Instrumentation and Equipment .....	5
SECTION 3 - Data Summary .....	6
SECTION 4 - Graphs .....	8
Wind Speed Time Series .....	9
Wind Speed Distributions .....	10
Monthly Average Wind Speeds .....	10
Diurnal Average Wind Speeds .....	11
Turbulence Intensities .....	11
Wind Roses .....	12
SECTION 5 - Significant Meteorological Events .....	12
SECTION 6 - Data Collection and Maintenance .....	13
SECTION 7 - Data Recovery and Validation .....	13
Test Definitions .....	13
Sensor Statistics .....	14
APPENDIX A - Sensor Performance Report .....	16
Test Definitions .....	16
Sensor Statistics .....	17
APPENDIX B - Plot Data .....	18
Wind Speed Distribution Data .....	18
Diurnal Average Wind Speed Data .....	19
Monthly Average Wind Speed Data .....	20
Wind Rose Data .....	21

## TABLE OF FIGURES

Figure 1 - Location of the Swans Island Tower.....	5
Figure 2 – Wind Speed Time Series, September 1, 2008 – November 30, 2008 .....	9
Figure 3 – Wind Speed Distribution, September 1, 2008 – November 30, 2008 .....	10
Figure 4 – Monthly Average Wind Speed September 2007 – November 2008 .....	10
Figure 5 – Diurnal Average Wind Speed, September 1, 2008 – November 30, 2008.....	11
Figure 6 – Turbulence Intensity, September 1, 2008 – November 30, 2008.....	11
Figure 7 – Wind Rose, September 1, 2008 – November 30, 2008 .....	12

## EXECUTIVE SUMMARY

All the work presented in this Wind Data Report including installation and decommissioning of the meteorological tower and instrumentation, and the data analysis and reporting was performed by the Renewable Energy Research Laboratory (RERL) at the University of Massachusetts, Amherst.

This report summarizes the wind data recorded for the fall quarter, September 2008 through November 2008, at Swan's Island, ME. The fall months showed an overall increase in wind resource from the summer (this is expected). Average wind speeds for the quarter were found to be around 6-7 m/s at a height of 50m. The prevailing wind direction for the quarter was SW. The amount of valid data recorded for the quarter was 98%.

Additional information about interpreting the data presented in this report can be found in the Fact Sheet, "Interpreting Your Wind Resource Data," produced by RERL and the Massachusetts Technology Collaborative (MTC). This document is found through the RERL website:

[http://www.ceere.org/rerl/about\\_wind/RERL\\_Fact\\_Sheet\\_6\\_Wind\\_resource\\_interpretation.pdf](http://www.ceere.org/rerl/about_wind/RERL_Fact_Sheet_6_Wind_resource_interpretation.pdf)

\* 1 m/s = 2.237 mph.

## SECTION 1 - Station Location

The station is a cell phone tower operated by U.S. Cellular, located at Stockbridge Hill on Swans Island, Maine. The coordinates for the tower are 44.11161 N, 68.42218 W. The base of the tower is at an altitude of 54.86 m (180 ft) above mean sea level.



Figure 1 - Location of the Swans Island Tower

## SECTION 2- Instrumentation and Equipment

The wind monitoring equipment is mounted on the cell phone tower at a height of 50 m and 40 m. At each height 2 NRG #40 anemometers with standard calibration (Slope – 0.765 m/s, Offset – 0.350 m/s) and 1 NRG #200P wind vane are installed. A #110S temperature sensor is mounted at the base of the tower at an approximated height of 2 m. The data is logged by an NRG Symphonie logger and is mailed to the University of Massachusetts, Amherst on a regular basis. The logger samples wind speed and direction once every two seconds. These samples are combined into 10-minute averages and are put into a binary file along with the standard deviation for each 10-minute interval. The binary files are converted to ASCII text files using the NRG software BaseStation®.

These text files are then imported into a database software program where they are subjected to quality assurance tests prior to data usage.

### SECTION 3- Data Summary

A summary of the wind speeds and wind directions measured during the reporting period is included in Table 1. Table 1 includes the mean wind speeds measured at each measurement height, the maximum instantaneous wind speed measured at each measurement height and the prevailing wind direction measured at each measurement height. These values are provided for each month of the reporting period and for the whole reporting period.

**Table 1. Wind Speed and Direction Data Summary**

<b>Date</b>	<b>Mean Wind Speed</b>	<b>Max Wind Speed</b>	<b>Prevailing Wind Direction</b>	<b>Mean Wind Speed</b>	<b>Max Wind Speed</b>	<b>Prevailing Wind Direction</b>
<b>Height Units</b>	<b>50 m [m/s]</b>	<b>50 m [m/s]</b>	<b>50 m</b>	<b>40 m [m/s]</b>	<b>40 m [m/s]</b>	<b>40 m</b>
Sept 2008	5.92	15.42	SW	5.44	14.38	SSW
Oct 2008	6.68	23.74	N	6.21	22.01	NNW
Nov 2008	7.21	22.66	NW	6.59	21	NW
<b>Sept 2008 -Nov 2008</b>	<b>6.6</b>	<b>23.74</b>	<b>SW</b>	<b>6.08</b>	<b>22.01</b>	<b>SSW</b>

Wind data statistics in the table are reported when more than 90% of the data during the reporting period are valid. In cases when larger amounts of data are missing, the percent of the available data that are used to determine the data statistics is noted. For this quarter, the percent of available data was 98.02%.

No measurement of wind speed or direction can be perfectly accurate. Wind speed measurement errors occur due to anemometer manufacturing variability, anemometer calibration errors, the response of anemometers to turbulence and vertical air flow and due to air flows caused by the anemometer mounting system. Every effort is made to reduce the sources of these errors. Nevertheless, the values reported in this report have an expected uncertainty of about  $\pm 2\%$  or  $\pm 0.2$  m/s, whichever is greater. Wind direction measurement errors occur due to sensor measurement uncertainty, tower effects, boom alignment measurement errors and twisting of pipe sections during the raising of a pipe tower. Efforts are also made to reduce these errors, but the reported wind directions are estimated to have an uncertainty of  $\pm 5$  degrees.

A summary of the turbulence intensity and mean wind shear measured at each measurement height during the reporting period is included in Table 2. These values are provided for each month of the reporting period and for the whole reporting period. Turbulence Intensity is calculated by dividing the standard deviation of the wind speed by the mean wind speed and is a measure of the gustiness of a wind resource. Lower turbulence results in lower mechanical loads on a wind turbine. Turbulence intensity varies with wind speed. The average turbulence intensity presented in Table 2 is the mean turbulence intensity when the wind speed at each measurement height is between 10 and 11 m/s.

Shear coefficients provide a measure of the change in wind speed with height. When data at multiple heights are available, shear coefficients,  $\alpha$ , have been determined. They can be used in the following formula to estimate the average wind speed,  $U(z)$ , at height  $z$ , when the average wind speed,  $U(z_r)$ , at height  $z_r$  is known:

$$U(z) = U(z_r) \left( \frac{z}{z_r} \right)^\alpha$$

The change in wind speed with height is a very complicated relationship related to atmospheric conditions, wind speed, wind direction, time of day and time of year. This formula will not always provide the correct answer at any given site. Nevertheless the calculated shear coefficient, based on measurements at two heights, can be used to characterize the degree of increase in wind speed with height at a site.

The mean wind shear coefficient that is provided here is calculated based on the mean wind speeds in Table 1, where  $z_{high}$  and  $z_{low}$  are the heights of the higher and lower mean wind speeds used in the calculation and  $U(z_{low})$  and  $U(z_{high})$  are the mean wind speeds at the two heights.

$$\alpha = \log \left( \frac{U(z_{high})}{U(z_{low})} \right) / \log \left( \frac{z_{high}}{z_{low}} \right)$$



**Table 2. Shear and Turbulence Intensity Data Summary**

Date	Turbulence Intensity at 10 m/s	Turbulence Intensity at 10 m/s	Mean Wind Shear Coefficient, $\alpha$
Height Units	50 m [-]	40 m [-]	Between 50 m and 40 m [-]
Sept 2008	0.17	0.19	0.38
Oct 2008	0.16	0.18	0.33
Nov 2008	0.16	0.18	0.4
<b>Sept 2008 –Nov 2008</b>	<b>0.16</b>	<b>0.17</b>	<b>0.37</b>

## SECTION 4- Graphs

This report contains several types of wind data graphs. Unless otherwise noted, each graph represents data from 1 quarter (3 months). The following graphs are included:


- Time Series – 10-minute average wind speeds are plotted against time.
- Wind Speed Distribution – A histogram plot giving the percentage of time that the wind is at a given wind speed.
- Monthly Average – A plot of the monthly average wind speed over a 12-month period. This graph shows the trends in the wind speed over the year.
- Diurnal – A plot of the average wind speed for each hour of the day.
- Turbulence Intensity – A plot of turbulence intensity as a function of wind speed. Turbulence Intensity is calculated as the standard deviation of the wind speed divided by the wind speed and is a measure of the gustiness of a wind resource. Lower turbulence results in lower mechanical loads on a wind turbine.
- Wind Rose – A plot, by compass direction showing the percentage of time that the wind comes from a given direction and the average wind speed in that direction.

The time series shows the wind to stay around 6-7 m/s for the majority of the time with some peaks above 15 m/s. December shows significant time in the 10-15 m/s range. The monthly average wind speeds for the whole fall season stayed around 5-7 m/s. The

mean wind speeds hold very steady over the hours of the day. The wind rose displays the prevailing wind direction of SW with the strongest winds coming from the SE (approximately 8-9 m/s). The weakest winds approach from the NE with a fairly steady average from other directions.

Data for the wind speed histograms, monthly and diurnal average plots, and wind roses are included in APPENDIX B.

### Wind Speed Time Series



**Figure 2 – Wind Speed Time Series, September 1, 2008 – November 30, 2008**

## Wind Speed Distributions




Figure 3 – Wind Speed Distribution, September 1, 2008 – November 30, 2008

## Monthly Average Wind Speeds




Figure 4 – Monthly Average Wind Speed September 2007 – November 2008

## Diurnal Average Wind Speeds




Figure 5 – Diurnal Average Wind Speed, September 1, 2008 – November 30, 2008

## Turbulence Intensities





Figure 6 – Turbulence Intensity, September 1, 2008 – November 30, 2008

## Wind Roses



**Figure 7 – Wind Rose, September 1, 2008 – November 30, 2008**

## **SECTION 5- Significant Meteorological Events**

There were no significant meteorological events occurring in the region between September 2008 and November 2008. Overall, the fall was unusually wet in this area, which does not significantly effect wind resource measurement.

Source: <http://www.weather.gov/climate/index.php?wfo=car>

## SECTION 6 - Data Collection and Maintenance

There were no maintenance issues with the equipment for this quarter and data collection went well.

## SECTION 7 - Data Recovery and Validation

All raw wind data are subjected to a series of tests and filters to weed out data that are faulty or corrupted. Definitions of these quality assurance (QA) controls are given below under Test Definitions and Sensor Statistics. These control filters were designed to automate the quality control process and used many of the previous hand-worked data sets made at UMass to affect a suitable emulation. The gross percentage of data recovered (ratio of the number of raw data points received to data points expected) and net percentage (ratio of raw data points which passed all QA control tests to data points expected) are shown below.

Gross Data Recovered [%]	100
Net Data Recovered [%]	98.02

### Test Definitions

All raw data were subjected to a series of validation tests, as described below. The sensors tested and the parameters specific to each sensor are given in the Sensor Performance Report which is included in APPENDIX A. Data which were flagged as invalid were not included in the statistics presented in this report.

**MinMax Test:** All sensors are expected to report data values within a range specified by the sensor and logger manufacturers. If a value falls outside this range, it is flagged as invalid. A data value from the sensor listed in Test Field 1 (TF1) is flagged if it is less than Factor 1 (F1) or greater than Factor 2. This test has been applied to the following sensors (as applicable): wind speed, wind speed standard deviation, wind direction, temperature, and solar insolation.

$$F1 > TF1 > F2$$

**MinMaxT Test:** This is a MinMax test for wind direction standard deviation with different ranges applied for high and low wind speeds. A wind direction standard deviation data value (TF1) is flagged either if it is less than Factor 1, if the wind speed (TF2) is less than Factor 4 and the wind direction standard deviation is greater than Factor 2, or if the wind speed is greater than or equal to Factor 4 and the wind direction standard deviation is greater than Factor 3.

$$\begin{aligned}
 & (\text{TF1} < \text{F1}) \\
 & \text{or } (\text{TF2} < \text{F4} \text{ and } \text{TF1} > \text{F2}) \\
 & \text{or } (\text{TF2} \geq \text{F4} \text{ and } \text{TF1} > \text{F3})
 \end{aligned}$$

**Icing Test:** An icing event occurs when ice collects on a sensor and degrades its performance. Icing events are characterized by the simultaneous measurements of near-zero standard deviation of wind direction, non-zero wind speed, and near- or below-freezing temperatures. Wind speed, wind speed standard deviation, wind direction, and wind direction standard deviation data values are flagged if the wind direction standard deviation (CF1) is less than or equal to Factor 1 (F1), the wind speed (TF1) is greater than Factor 2 (F2), and the temperature (CF2) is less than Factor 3 (F3). To exit an icing event, the wind direction standard deviation must be greater than Factor 4.

$$\text{CF1} \leq \text{F1} \text{ and } \text{TF1} > \text{F2} \text{ and } \text{CF2} < \text{F3}$$

**CompareSensors Test:** Where primary and redundant sensors are used, it is possible to determine when one of the sensors is not performing properly. For anemometers, poor performance is characterized by low data values. Therefore, if one sensor of the pair reports values significantly below the other, the low values are flagged. At low wind speeds (Test Fields 1 and 2 less than or equal to Factor 3) wind speed data are flagged if the absolute difference between the two wind speeds is greater than Factor 1. At high wind speeds (Test Fields 1 or 2 greater than Factor 3) wind speed data are flagged if the absolute value of the ratio of the two wind speeds is greater is greater than Factor 2.

$$\begin{aligned}
 & [ \text{TF1} \leq \text{F3} \text{ and } \text{TF2} \leq \text{F3} \text{ and } \text{abs}(\text{TF1} - \text{TF2}) > \text{F1} ] \\
 & \text{or } [ (\text{TF1} > \text{F3} \text{ or } \text{TF2} > \text{F3}) \text{ and } (\text{abs}(1 - \text{TF1} / \text{TF2}) > \text{F2} \text{ or } \text{abs}(1 - \text{TF2} / \text{TF1}) > \text{F2}) ]
 \end{aligned}$$

### Sensor Statistics

A summary of the results of the data collection and filtering are given in the Sensor Performance Report which is included in APPENDIX A. The following categories of information, tabulated for each sensor, are included in that report.

**Expected Data Points:** the total number of sample intervals between the start and end dates (inclusive).

**Actual Data Points:** the total number of data points recorded between the start and end dates.

**% Data Recovered:** the ratio of actual and expected data points (this is the *gross data recovered percentage*).

**Hours Out of Range:** total number of hours for which data were flagged according to MinMax and MinMaxT tests. These tests flag data which fall outside of an expected range.

**Hours of Icing:** total number of hours for which data were flagged according to Icing tests. This test uses the standard deviation of wind direction, air temperature, and wind speed to determine when sensor icing has occurred.

**Hours of Fault:** total number of hours for which data were flagged according to CompareSensors tests. These tests compare two sensors (e.g. primary and redundant anemometers installed at the same height) and flag data points where one sensor differs significantly from the other.

**% Data Good:** the filter results are subtracted from the gross data recovery percentage to yield the *net data recovered percentage*.



# APPENDIX A - Sensor Performance Report

## Test Definitions

Test Order	TestField1	TestField2	TestField3	CalcField1	CalcField2	Calc Field3	Test Type	Factor 1	Factor 2	Factor 3	Factor 4
1	Anem50aMS						MinMax	0	90		
2	Anem50bMS						MinMax	0	90		
3	Anem40aMS						MinMax	0	90		
4	Anem40bMS						MinMax	0	90		
5	Anem50yMS						MinMax	0	90		
6	Anem40yMS						MinMax	0	90		
7	Vane50aDEG						MinMax	0	359.9		
8	Vane40aDEG						MinMax	0	359.9		
9	Etemp2aDEGF						MinMax	-30	60		
10	Batt2aVDC						MinMax	10.5	15		
11	Turb50zNONE						MinMax	0	2		
12	Turb40zNONE						MinMax	0	2		
13	AnemSD50aMS						MinMax	0	4		
14	AnemSD50bMS						MinMax	0	4		
15	AnemSD40aMS						MinMax	0	4		
16	AnemSD40bMS						MinMax	0	4		
17	AnemSD50yMS						MinMax	0	4		
18	AnemSD40yMS						MinMax	0	4		
21	EtempSD2aDEGF						MinMax	-30	60		
22	BattSD2aVDC						MinMax	0	5		
200	VaneSD50aDEG	Anem50y MS					MinMax T	0	100	100	10
201	VaneSD40aDEG	Anem40y MS					MinMax T	0	100	100	10
300	Anem50aMS	AnemSD50a MS	Vane50a DEG	VaneSD50a DEG	Etemp2aDE GF		Icing	0.5	1	2	4
301	Anem50bMS	AnemSD50b MS	Vane50a DEG	VaneSD50a DEG	Etemp2aDE GF		Icing	0.5	1	2	4
302	Anem40aMS	AnemSD40a MS	Vane40a DEG	VaneSD40a DEG	Etemp2aDE GF		Icing	0.5	1	2	4
303	Anem40bMS	AnemSD40b MS	Vane40a DEG	VaneSD40a DEG	Etemp2aDE GF		Icing	0.5	1	2	4
304	Anem50yMS	AnemSD50y MS	Vane50a DEG	VaneSD50a DEG	Etemp2aDE GF		Icing	0.5	1	2	4
305	Anem40yMS	AnemSD40y MS	Vane40a DEG	VaneSD40a DEG	Etemp2aDE GF		Icing	0.5	1	2	4
400	Anem50aMS	Anem50b MS					Compare Sensors	1	0.25	3	0
401	Anem40aMS	Anem40b MS					Compare Sensors	1	0.25	3	0

### Sensor Statistics

Sensor	Expected Data Points	Actual Data Points	% Data Recovered	Hours Out of Range	Hours of Icing	Hours of Fault	% Data Good
Anem50aMS	12961	12961	100	3.5	0.667	137.667	93.434
Anem50bMS	12961	12961	100	0.167	0.667	65.5	96.929
Anem40aMS	12961	12961	100	2.5	0.333	126.833	93.997
Anem40bMS	12961	12961	100	0.5	0.333	43.5	97.948
Vane50aDEG	12961	12961	100	0.333	0.667	0	99.954
Vane40aDEG	12961	12961	100	0.333	0.333	0	99.969
Etemp2aDEGF	12961	12961	100	0	0	0	100
Anem50yMS	12961	12961	100	0	0.667	0	99.969
Anem40yMS	12961	12961	100	0	0.333	0	99.985
<b>Total</b>	<b>116649</b>	<b>116649</b>	<b>100</b>	<b>7.333</b>	<b>4</b>	<b>373.5</b>	<b>98.021</b>

## APPENDIX B - Plot Data

### Wind Speed Distribution Data

Wind Speed [m/s]	Time [%]
0.5	0.53
1.5	1.89
2.5	4.56
3.5	9.23
4.5	14.02
5.5	17.31
6.5	15.63
7.5	11.27
8.5	8.08
9.5	5.58
10.5	3.8
11.5	2.79
12.5	1.93
13.5	1.43
14.5	0.76
15.5	0.34
16.5	0.24
17.5	0.12
18.5	0.11
19.5	0.14
20.5	0.18
21.5	0.02
22.5	0.02
23.5	0.01
24.5	0

### Diurnal Average Wind Speed Data

Hour of day	Wind Speed [m/s]
0.5	6.68
1.5	6.56
2.5	6.44
3.5	6.44
4.5	6.55
5.5	6.66
6.5	6.51
7.5	6.37
8.5	6.26
9.5	6.23
10.5	6.35
11.5	6.41
12.5	6.36
13.5	6.37
14.5	6.4
15.5	6.53
16.5	6.64
17.5	6.8
18.5	6.9
19.5	7.11
20.5	6.95
21.5	6.98
22.5	7.05
23.5	6.9

### **Monthly Average Wind Speed Data**

<b>Month</b>	<b>50 m Mean Wind Speed [m/s]</b>
September 2007	5.88
October 2007	6.25
November 2007	7.34
December 2007	7.42
January 2008	7.63
February 2008	6.85
March 2008	7.64
April 2008	6.33
May 2008	6.34
June 2008	5.16
July 2008	5.75
August 2008	4.9
September 2008	5.92
October 2008	6.68
November 2008	7.21

### Wind Rose Data

<b>Wind Direction</b>	<b>Mean Wind Speed [m/s]</b>	<b>Percent of Time [%]</b>
N	6.78	10
NNE	6.39	5.33
NE	6.14	3.72
ENE	5.71	2.63
E	5.47	4.75
ESE	6.09	3.38
SE	8.55	3.17
SSE	7.77	3.82
S	6.91	4.96
SSW	6.88	7.67
SW	6.53	12.38
WSW	6.42	8.13
W	6.55	5.83
WNW	6.67	6.72
NW	6.62	7.94
NNW	6.41	9.57